

CLI JC6100 Series Universal Client

Everything You Need in a Slender Form

The JC6100's robust platform is ready to handle any task. Its enclosure is assembled from precision rugged aluminum, which makes it ready for harsh environments. With a dual core AMD G-Series processor running at 1 GHz and a Radeon HD 6290 GPU, it has performance features needed to handle the most complex VDI environments. Delivering custom or unique peripheral support with one PS/2, 4 USB, one DVI-I port, and one DVI-D port. VGA adapter is included. The JC6100 has the tools and features required for deployment into the most demanding of virtual environments.

Rugged Client for Demanding Environments

The JC6100 is built with the latest embedded technology from AMD, utilizing the fastest available G-Series processor to run the latest in Operating Systems and applications. With a dedicated GPU, it delivers an unprecedented graphics performance in a thin client device. All of these features are packaged with a small form factor and no moving parts. With the JC6100, the future of thin computing is here today.

At a Glance

The JC6100 is a ruggedized client that is built to withstand the most inclement environments. With support for the latest OS offerings from Microsoft and Ubuntu, the JC6100 is ready for deployment from application delivery to legacy terminal emulation.

Features

- Dual core 1.0 GHz processor
- Dual Digital Video (DVI-D and DVI-I).
- Dedicated Radeon HD 6290 GPU.
- Multiple mounting options.
- Energy efficient, robust feature set, maximum performance.



CLI JC6100 Ruggedized Slim Client

Modular logic unit, AMD G-Series 1.0 GHz CPU Dual Core, Gigabit Ethernet, 4 USB 2.0 ports, PS/2 keyboard/mouse ports, audio in/out ports, external power supply, socketed DRAM and Industrial grade SSD Flash, security lock slot, per seat license for CLI Device Manager software, three-year return-to-depot warranty.

CONFIGURATION	DESCRIPTION	JC6100H	JC6100W	JC6100L	JC6100C
Operating system	Customize your JC6100 with Windows Embedded Standard 2009, WES7 or Embedded Linux Contact your Reseller or CLI Sales Representative for Custom Operating System Configurations	CE6	WES7 32-bit/64-bit	Linux	CLI Custom Cloud OS
Processor	AMD G-Series T40N (1.0 GHz) Dual Core				
Chipset	A50M				
Video	AMD Radeon HD 6290 Up to 1920 x 1200 Wide Screen Resolution; 32-bit Color 64MB - 512MB Shared Memory (1)DVI-D, (1) DVI-I, (1) VGA Adapter Included.				
Memory	(1) DDR3 - 1333 SODIMM	Min: 1GB Max: 2GB	Min: 1GB Max: 4GB	2GB	1GB
Flash	Industrial Grade SATA SSD Flash Module	1GB	Min: 8GB Max: 32GB	8GB	1GB
Ruggedized Slim Design	Equipped with an Industrial Strength Rugged Aluminum Case				
Communications	(1) Gigabit Ethernet port				
Ports and Connectors	(4) USB 2.0 Ports (2 Front, 2 Rear),(1)DVI-D and (1) DVI-I (1) PS2, (1) RJ-45/Ethernet, (1) Mic-In Jack, (1) Audio Out Jack				
Wireless	Optional External USB Wireless Adapter	JC6160H	JC6160W	JC6160L	JC6160C
Operating temperature	0 °C to 40 °C 20% to 80% Non-Condensing Humidity				
Protocols	RDP, ICA, X Client, VNC (Remote Shadowing), PXE, Quest, VMware View, Web Browser				
Full Weight	1.7 lbs				
Dimensions	(w x d x h) 7.88 in (at front) x 5.3 in x 1.9 in				

CLI, Inc. 580 South Melrose Street Placentia, CA 92870

info@computerlab.com | 1 800 727-5250 | www.computerlab.com

© 2015 CLI, Inc. All rights reserved. Specifications are subject to change without notice. CLI is a registered trademark. All other trademarks are the property of their respective owners. CLI shall not be liable for technical or editorial errors or omissions contained herein.

