DASCOM

2610+



Highlights at a Glance:

- Print Speeds up to 680 cps
- 20,000 Pages per Month Workload
- 136 columns
- 24 pin Print Head produces excellent print quality
- Straight through paper path for easy forms loading
- Ethernet, Parallel and USB interfaces standard
- LCD Display



The Tally Dascom T2610+ is a highly featured, reliable and stylish machine. Performance and workload, ergonomics, maintainability, excellent price - everything has been incorporated to ensure it is the only acceptable choice for the customer.

Continuous and cut forms are fed at the front for quick and easy loading. This ensures a straight path for the forms resulting in a reliable paper transportation, even on 6-part stock. Loading the paper is easier. The operator does not have to fumble over or around the printer to gain access to rear located tractors. User intervention is kept at a minimum with a suite of features designed to ensure the products run at optimum reliability and performance.

The product is at home in the computer room, or in the office. An unobtrusive 52 dbA acoustic rating results in a printer, which is half as quiet, compared with many competitive models.

Intelligent Mail Barcode - be sure your printer has this important feature

The US Postal Service bar code standard will require this capability to take advantage of the best rates available.

Intelligent Mail Barcode sample

իլիվեսելիլիվիրիկիսվիկելիրերեսվիրվիլի



2610+

Resolutionup to 360 x 360 dpiCharacter Density10, 12, 15, 171, 20 cpiLine Density2, 3, 4, 6, 8, 12 lpiPrint Head Life500 million dots per wireMemory256 kBStandard ConnectivityParallel (Bi-directional), USB 2.0 and Ethernet (10/100 BaseT)Optional ConnectivitySerial RS-232Standard EmulationIBM ProPrinter XL24, Epson ESC/P2, MTPL + Barcode + LCPFontsHS Draft, Draft, Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B, 14 Barcodes and large character printingConsumableRibbon: 9 million charactersStandard Paper HandlingOne tractor useable as push (front or rear) or pull (top) version, continuous paper with straight paper path and park position, cut sheet front insertion, tear or front offOptional Paper HandlingAdditional push tractor (rear),Number of CopiesPush tractor front: 1 original + 5 copies; Pull tractor top: 20 g/m²Paper Weight60-120 g/m²Paper Weight8.6 kg, 18.9 lbsPhysical SizeWidth: 76 to 278 mm, 3.0 to 1.0 in; Length: 76 to 599 mm, 3.0 to 23.6 inPhysical Size458 x 265 x 200 mm, 18.0 x 10.4 x 7.9 in (W x D x H)Acoustic52 dB(A)Power Voltage100 - 240 V wide range auto-sensingPower Voltage100 - 240 V wide range auto-sensingPower Voltage100 - 240 V wide range auto-sensingPower Voltage100 or 240 V wide range auto-sensingPower Voltage100 were; 10% to 85% humi	Print Speed	680 cps (Fastest Draft); 500 cps (HS-Draft), 333 cps (Draft), 111 cps (LQ) at 10 cpi
Line Density2, 3, 4, 6, 8, 12 lpiPrint Head Life500 million dots per wireMemory256 kBStandard ConnectivityParallel (Bi-directional), USB 2.0 and Ethernet (10/100 BaseT)Optional ConnectivitySerial RS-232Standard EmulationIBM ProPrinter XL24, Epson ESC/P2, MTPL + Barcode + LCPFontsHS Draft, Draft, Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B, 14 Barcodes and large character printingConsumableRibbon: 9 million charactersStandard Paper HandlingOne tractor useable as push (front or rear) or pull (top) version, continuous paper with straight paper path and park position, cut sheet front insertion, tear or front offOptional Paper HandlingAdditional push tractor (rear), Pult tractor top: 1 original + 5 copies; Pull tractor top: 1 original + 5 copiesPaper TypeCut sheets, continuous forms, multi-part formsPaper SizeWidth: 76 to 278 mm, 3.0 to 11.0 in; Length: 76 to 599 mm, 3.0 to 23.6 in Physical SizePhysical Size458 x 265 x 200 mm, 18.0 x 10.4 x 7.9 in (W x D x H)Acoustic52 dB(A)Power Consumption40 Watt Printing; <10 W Sleep ModeTemperature+10° to +40° C; 10% to 85% humidityWorkload20.000 pages per monthMTBF15.000 hoursDriversWindows 2000/XP/Vista/7/8/10 and Server 2003/2008; SAP	Resolution	up to 360 x 360 dpi
Print Head Life500 million dots per wireMemory256 kBStandard ConnectivityParallel (Bi-directional), USB 2.0 and Ethernet (10/100 BaseT)Optional ConnectivitySerial RS-232Standard EmulationIBM ProPrinter XL24, Epson ESC/P2, MTPL + Barcode + LCPFontsHS Draft, Draft, Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B, 14 Barcodes and large character printingConsumableRibbon: 9 million charactersStandard Paper HandlingOne tractor useable as push (front or rear) or pull (top) version, continuous paper with straight paper path and park position, cut sheet front insertion, tear or front offOptional Paper HandlingAdditional push tractor (rear), Push tractor front: 1 original + 5 copies; Pull tractor top: 1 original + 5 copies; Pull tractor top: 1 original + 5 copies; Pull tractor top: 1 original + 5 copies; Paper WeightEast 200 mm, 3.0 to 11.0 in; Length: 76 to 599 mm, 3.0 to 23.6 inPhysical Weight8.6 kg, 18.9 lbsPhysical Size458 x 265 x 200 mm, 18.0 x 10.4 x 7.9 in (W x D x H)Acoustic52 dB(A)Power Voltage100 - 240 V wide range auto-sensingPower Consumption40 Watt Printing; <10 W Sleep Mode	Character Density	10, 12, 15, 17.1, 20 cpi
Memory 256 kB Standard Connectivity Parallel (Bi-directional), USB 2.0 and Ethernet (10/100 BaseT) Optional Connectivity Serial RS-232 Standard Emulation IBM ProPrinter XL24, Epson ESC/P2, MTPL + Barcode + LCP Fonts HS Draft, Draft, Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B, 14 Barcodes and large character printing Consumable Ribbon: 9 million characters Standard Paper Handling One tractor useable as push (front or rear) or pull (top) version, continuous paper with straight paper path and park position, cut sheet front insertion, tear or front off Optional Paper Handling Additional push tractor (rear), Push tractor front: 1 original + 5 copies; Pull tractor top: 1 original + 5 copies; Pull tractor top: 1 original + 5 copies; Pull tractor top: 1 original + 5 copies Paper Type Cut sheets, continuous forms, multi-part forms Paper Weight 60-120 g/m² Paper Size Width: 76 to 278 mm, 3.0 to 11.0 in; Length: 76 to 599 mm, 3.0 to 23.6 in Physical Weight 8.6 kg, 18.9 lbs Physical Size 458 x 265 x 200 mm, 18.0 x 10.4 x 7.9 in (W x D x H) Accoustic 52 dB(A) Power Voltage 100 - 240 V wide range auto-sensing Power Voltage 100 - 240 V wide range auto-sensing Power Consumption 40 Watt Printing; <10 W	Line Density	2, 3, 4, 6, 8, 12 lpi
Standard ConnectivityParallel (Bi-directional), USB 2.0 and Ethernet (10/100 BaseT)Optional ConnectivitySerial RS-232Standard EmulationIBM ProPrinter XL24, Epson ESC/P2, MTPL + Barcode + LCPFontsHS Draft, Draft, Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B, 14 Barcodes and large character printingConsumableRibbon: 9 million charactersStandard Paper HandlingOne tractor useable as push (front or rear) or pull (top) version, continuous paper with straight paper path and park position, cut sheet front insertion, tear or front offOptional Paper HandlingAdditional push tractor (rear), Push tractor front: 1 original + 5 copies; Pull tractor tor: 1 original + 5 copies; Pull tractor tor: 1 original + 5 copies; Pull tractor front: 1 original + 5 copies; Pull tractor tor: 1 original + 5 copies; Pull tractor form: Paper SizePaper SizeWidth: 76 to 278 mm, 3.0 to 11.0 in; Length: 76 to 599 mm, 3.0 to 23.6 in Physical SizePhysical Size458 x 265 x 200 mm, 18.0 x 10.4 x 7.9 in (W x D x H) AcousticAcoustic52 dB(A)Power Consumption40 Watt Printing; <10 W Sleep Mode TemperatureTemperature+10° to +40° C; 10% to 85% humidityWorkload20.000 pages per monthMTBF15.000 hoursDriversWindows 2000/XP/Vista/7/B/10 and Server 2003/2008; SAP	Print Head Life	500 million dots per wire
Optional ConnectivitySerial RS-232Standard EmulationIBM ProPrinter XL24, Epson ESC/P2, MTPL + Barcode + LCPFontsHS Draft, Draft, Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B, 14 Barcodes and large character printingConsumableRibbon: 9 million charactersStandard Paper HandlingOne tractor useable as push (front or rear) or pull (top) version, continuous paper with straight paper path and park position, cut sheet front insertion, tear or front offOptional Paper HandlingAdditional push tractor (rear), Push tractor front: 1 original + 5 copies; Pull tractor top: 1 original + 5 copies; Pull tractor top: 1 original + 5 copiesPaper TypeCut sheets, continuous forms, multi-part formsPaper SizeWidth: 76 to 278 mm, 3.0 to 11.0 in; Length: 76 to 599 mm, 3.0 to 23.6 in Physical SizePhysical Size458 x 265 x 200 mm, 18.0 x 10.4 x 7.9 in (W x D x H)Acoustic52 dB(A)Power Consumption40 Watt Printing; <10 W Sleep ModeTemperature+10° to +40° C; 10% to 85% humidityWorkload20.000 pages per monthMTBF15.000 hoursDriversWindows 2000/XP/Vista/7/8/10 and Server 2003/2008; SAP	Memory	256 kB
Standard EmulationIBM ProPrinter XL24, Epson ESC/P2, MTPL + Barcode + LCPFontsHS Draft, Draft, Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B, 14 Barcodes and large character printingConsumableRibbon: 9 million charactersStandard Paper HandlingOne tractor useable as push (front or rear) or pull (top) version, continuous paper with straight paper path and park position, cut sheet front insertion, tear or front offOptional Paper HandlingAdditional push tractor (rear), Push tractor front: 1 original + 5 copies; Pull tractor top: 1 original + 5 copies; Pull tractor top: 1 original + 5 copies; Pull tractor top: 1 original + 5 copiesPaper TypeCut sheets, continuous forms, multi-part formsPaper SizeWidth: 76 to 278 mm, 3.0 to 11.0 in; Length: 76 to 599 mm, 3.0 to 23.6 in Physical SizePhysical Size458 x 265 x 200 mm, 18.0 x 10.4 x 7.9 in (W x D x H)Accoustic52 dB(A)Power Consumption40 Watt Printing; <10 W Sleep Mode	Standard Connectivity	Parallel (Bi-directional), USB 2.0 and Ethernet (10/100 BaseT)
FontsHS Draft, Draft, Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B, 14 Barcodes and large character printingConsumableRibbon: 9 million charactersStandard Paper HandlingOne tractor useable as push (front or rear) or pull (top) version, continuous paper with straight paper path and park position, cut sheet front insertion, tear or front offOptional Paper HandlingAdditional push tractor (rear), Push tractor top: 1 original + 5 copies; Pull tractor top: 1 original + 5 copies; Pull tractor top: 1 original + 5 copies; Pull tractor top: 1 original + 5 copiesPaper TypeCut sheets, continuous forms, multi-part forms Paper SizePaper SizeWidth: 76 to 278 mm, 3.0 to 11.0 in; Length: 76 to 599 mm, 3.0 to 23.6 in Physical SizePhysical Size458 x 265 x 200 mm, 18.0 x 10.4 x 7.9 in (W x D x H) AcousticAcoustic52 dB(A) Power VoltagePower Consumption40 Watt Printing; <10 W Sleep Mode	Optional Connectivity	Serial RS-232
and large character printingConsumableRibbon: 9 million charactersStandard Paper HandlingOne tractor useable as push (front or rear) or pull (top) version, continuous paper with straight paper path and park position, cut sheet front insertion, tear or front offOptional Paper HandlingAdditional push tractor (rear),Number of CopiesPush tractor front: 1 original + 5 copies; Pull tractor top: 1 original + 5 copies; Cut sheet: 1 original + 5 copiesPaper TypeCut sheets, continuous forms, multi-part formsPaper SizeWidth: 76 to 278 mm, 3.0 to 11.0 in; Length: 76 to 599 mm, 3.0 to 23.6 inPhysical Weight8,6 kg, 18,9 lbsPhysical Size458 x 265 x 200 mm, 18.0 x 10.4 x 7.9 in (W x D x H)Acoustic52 dB(A)Power Voltage100 - 240 V wide range auto-sensingPower Consumption40 Watt Printing; <10 W Sleep Mode	Standard Emulation	IBM ProPrinter XL24, Epson ESC/P2, MTPL + Barcode + LCP
ConsumableRibbon: 9 million charactersStandard Paper HandlingOne tractor useable as push (front or rear) or pull (top) version, continuous paper with straight paper path and park position, cut sheet front insertion, tear or front offOptional Paper HandlingAdditional push tractor (rear), Push tractor front: 1 original + 5 copies; Pull tractor top: 1 original + 5 copies; Pull tractor top: 1 original + 5 copies; Pull tractor top: 1 original + 5 copiesPaper TypeCut sheets, continuous forms, multi-part forms Paper Weight60-120 g/m²Paper SizeWidth: 76 to 278 mm, 3.0 to 11.0 in; Length: 76 to 599 mm, 3.0 to 23.6 in Physical Size458 x 265 x 200 mm, 18.0 x 10.4 x 7.9 in (W x D x H)Acoustic52 dB(A)Power Voltage100 - 240 V wide range auto-sensing Power Consumption40 Watt Printing; <10 W Sleep Mode	Fonts	HS Draft, Draft, Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B, 14 Barcodes
Standard Paper HandlingOne tractor useable as push (front or rear) or pull (top) version, continuous paper with straight paper path and park position, cut sheet front insertion, tear or front offOptional Paper HandlingAdditional push tractor (rear), Push tractor front: 1 original + 5 copies; Pull tractor top: 1 original + 5 copies; Pull tractor top: 1 original + 5 copies; Pull tractor top: 1 original + 5 copiesPaper TypeCut sheets, continuous forms, multi-part formsPaper Weight60-120 g/m²Paper SizeWidth: 76 to 278 mm, 3.0 to 11.0 in; Length: 76 to 599 mm, 3.0 to 23.6 in Physical SizePhysical Size458 x 265 x 200 mm, 18.0 x 10.4 x 7.9 in (W x D x H)Acoustic52 dB(A)Power Voltage100 - 240 V wide range auto-sensingPower Consumption40 Watt Printing; <10 W Sleep Mode		and large character printing
straight paper path and park position, cut sheet front insertion, tear or front offOptional Paper Handling Number of CopiesAdditional push tractor (rear), Push tractor front: 1 original + 5 copies; Pull tractor top: 1 original + 5 copies; Cut sheet: 1 original + 5 copiesPaper TypeCut sheets, continuous forms, multi-part formsPaper Weight60-120 g/m²Paper SizeWidth: 76 to 278 mm, 3.0 to 11.0 in; Length: 76 to 599 mm, 3.0 to 23.6 in Physical WeightPhysical Size458 x 265 x 200 mm, 18.0 x 10.4 x 7.9 in (W x D x H)Acoustic52 dB(A)Power Voltage100 - 240 V wide range auto-sensingPower Consumption40 Watt Printing; <10 W Sleep Mode	Consumable	Ribbon: 9 million characters
Optional Paper HandlingAdditional push tractor (rear),Number of CopiesPush tractor front: 1 original + 5 copies; Pull tractor top: 1 original + 5 copies; Cut sheet: 1 original + 5 copiesPaper TypeCut sheets, continuous forms, multi-part formsPaper Weight60-120 g/m²Paper SizeWidth: 76 to 278 mm, 3.0 to 11.0 in; Length: 76 to 599 mm, 3.0 to 23.6 inPhysical Weight8,6 kg, 18.9 lbsPhysical Size458 x 265 x 200 mm, 18.0 x 10.4 x 7.9 in (W x D x H)Acoustic52 dB(A)Power Voltage100 - 240 V wide range auto-sensingPower Consumption40 Watt Printing; <10 W Sleep ModeTemperature+10° to +40° C; 10% to 85% humidityWorkload20.000 pages per monthMTBF15.000 hoursDriversWindows 2000/XP/Vista/7/8/10 and Server 2003/2008; SAP	Standard Paper Handling	One tractor useable as push (front or rear) or pull (top) version, continuous paper with
Number of CopiesPush tractor front: 1 original + 5 copies; Pull tractor top: 1 original + 5 copies; Cut sheet: 1 original + 5 copies; Cut sheet: 1 original + 5 copiesPaper TypeCut sheets, continuous forms, multi-part formsPaper Weight60-120 g/m²Paper SizeWidth: 76 to 278 mm, 3.0 to 11.0 in; Length: 76 to 599 mm, 3.0 to 23.6 inPhysical Weight8,6 kg, 18.9 lbsPhysical Size458 x 265 x 200 mm, 18.0 x 10.4 x 7.9 in (W x D x H)Acoustic52 dB(A)Power Voltage100 - 240 V wide range auto-sensingPower Consumption40 Watt Printing; <10 W Sleep Mode		straight paper path and park position, cut sheet front insertion, tear or front off
Pull tractor top: 1 original + 5 copies; Cut sheet: 1 original + 5 copiesPaper TypeCut sheets, continuous forms, multi-part formsPaper Weight60-120 g/m²Paper SizeWidth: 76 to 278 mm, 3.0 to 11.0 in; Length: 76 to 599 mm, 3.0 to 23.6 inPhysical Weight8,6 kg, 18.9 lbsPhysical Size458 x 265 x 200 mm, 18.0 x 10.4 x 7.9 in (W x D x H)Acoustic52 dB(A)Power Voltage100 - 240 V wide range auto-sensingPower Consumption40 Watt Printing; <10 W Sleep Mode	Optional Paper Handling	Additional push tractor (rear),
sheet: 1 original + 5 copiesPaper TypeCut sheets, continuous forms, multi-part formsPaper Weight60-120 g/m²Paper SizeWidth: 76 to 278 mm, 3.0 to 11.0 in; Length: 76 to 599 mm, 3.0 to 23.6 inPhysical Weight8,6 kg, 18.9 lbsPhysical Size458 x 265 x 200 mm, 18.0 x 10.4 x 7.9 in (W x D x H)Acoustic52 dB(A)Power Voltage100 - 240 V wide range auto-sensingPower Consumption40 Watt Printing; <10 W Sleep Mode	Number of Copies	Push tractor front: 1 original + 5 copies;
Paper TypeCut sheets, continuous forms, multi-part formsPaper Weight60-120 g/m²Paper SizeWidth: 76 to 278 mm, 3.0 to 11.0 in; Length: 76 to 599 mm, 3.0 to 23.6 inPhysical Weight8,6 kg, 18.9 lbsPhysical Size458 x 265 x 200 mm, 18.0 x 10.4 x 7.9 in (W x D x H)Acoustic52 dB(A)Power Voltage100 - 240 V wide range auto-sensingPower Consumption40 Watt Printing; <10 W Sleep Mode		Pull tractor top: 1 original + 5 copies; Cut
Paper Weight 60-120 g/m² Paper Size Width: 76 to 278 mm, 3.0 to 11.0 in; Length: 76 to 599 mm, 3.0 to 23.6 in Physical Weight 8,6 kg, 18.9 lbs Physical Size 458 x 265 x 200 mm, 18.0 x 10.4 x 7.9 in (W x D x H) Acoustic 52 dB(A) Power Voltage 100 - 240 V wide range auto-sensing Power Consumption 40 Watt Printing; <10 W Sleep Mode		sheet: 1 original + 5 copies
Paper Size Width: 76 to 278 mm, 3.0 to 11.0 in; Length: 76 to 599 mm, 3.0 to 23.6 in Physical Weight 8,6 kg, 18.9 lbs Physical Size 458 x 265 x 200 mm, 18.0 x 10.4 x 7.9 in (W x D x H) Acoustic 52 dB(A) Power Voltage 100 - 240 V wide range auto-sensing Power Consumption 40 Watt Printing; <10 W Sleep Mode	Paper Type	Cut sheets, continuous forms, multi-part forms
Physical Weight 8,6 kg, 18.9 lbs Physical Size 458 x 265 x 200 mm, 18.0 x 10.4 x 7.9 in (W x D x H) Acoustic 52 dB(A) Power Voltage 100 - 240 V wide range auto-sensing Power Consumption 40 Watt Printing; <10 W Sleep Mode Temperature +10° to +40° C; 10% to 85% humidity Workload 20.000 pages per month MTBF 15.000 hours Drivers Windows 2000/XP/Vista/7/8/10 and Server 2003/2008; SAP	Paper Weight	60-120 g/m ²
Physical Size 458 x 265 x 200 mm, 18.0 x 10.4 x 7.9 in (W x D x H) Acoustic 52 dB(A) Power Voltage 100 - 240 V wide range auto-sensing Power Consumption 40 Watt Printing; <10 W Sleep Mode Temperature +10° to +40° C; 10% to 85% humidity Workload 20.000 pages per month MTBF 15.000 hours Drivers Windows 2000/XP/Vista/7/8/10 and Server 2003/2008; SAP	Paper Size	Width: 76 to 278 mm, 3.0 to 11.0 in; Length: 76 to 599 mm, 3.0 to 23.6 in
Acoustic52 dB(A)Power Voltage100 - 240 V wide range auto-sensingPower Consumption40 Watt Printing; <10 W Sleep Mode		8,6 kg, 18.9 lbs
Power Voltage100 - 240 V wide range auto-sensingPower Consumption40 Watt Printing; <10 W Sleep Mode	Physical Size	458 x 265 x 200 mm, 18.0 x 10.4 x 7.9 in (W x D x H)
Power Consumption40 Watt Printing; <10 W Sleep Mode	Acoustic	52 dB(A)
Temperature +10° to +40° C; 10% to 85% humidity Workload 20.000 pages per month MTBF 15.000 hours Drivers Windows 2000/XP/Vista/7/8/10 and Server 2003/2008; SAP	Power Voltage	
Workload20.000 pages per monthMTBF15.000 hoursDriversWindows 2000/XP/Vista/7/8/10 and Server 2003/2008; SAP	Power Consumption	40 Watt Printing; <10 W Sleep Mode
MTBF 15.000 hours Drivers Windows 2000/XP/Vista/7/8/10 and Server 2003/2008; SAP	Temperature	+10° to +40° C; 10% to 85% humidity
Drivers Windows 2000/XP/Vista/7/8/10 and Server 2003/2008; SAP	Workload	
	MTBF	
Warranty One year return to depot	Drivers	Windows 2000/XP/Vista/7/8/10 and Server 2003/2008; SAP
	Warranty	One year return to depot

DASCOM Americas

34 Lakeview Court Verona, Virginia 24482 Tel: (877) 434-1377 www.dascomamericas.com SERIAL MATRIX PRINTERS MOBILE PRINTERS FLATBED PRINTERS THERMAL PRINTERS

Copyright † 2018 DASCOM Americas Corporation. All rights reserved. All company and product names are trademarks of their respective owner Specifications are subject to change without notice. v3 | May 2018